Exhibit 2

(12) United States Patent Li et al.

(10) Patent No.: US 11,154,384 B2

(45) **Date of Patent:** Oct. 26, 2021

(54) MULTILAYER DENTAL APPLIANCES AND RELATED METHODS AND SYSTEMS

(71) Applicant: **ALIGN TECHNOLOGY, INC.**, San Jose, CA (US)

(72) Inventors: Chunhua Li, Cupertino, CA (US); Yan Chen, Cupertino, CA (US); Heinz Pudleiner, Krefeld (DE); Klaus Meyer, Dormagen (DE); Joerg Nickel,

Dormagen (DE); Craig Pehlert, Lenox, MA (US)

(73) Assignee: Align Technology, Inc., San Jose, CA

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 17/214,487

(22) Filed: Mar. 26, 2021

(65) Prior Publication Data

US 2021/0212802 A1 Jul. 15, 2021

Related U.S. Application Data

- (60) Continuation of application No. 15/476,655, filed on Mar. 31, 2017, now Pat. No. 10,973,613, which is a (Continued)
- (51) Int. Cl.

 A61C 7/08 (2006.01)

 B32B 27/28 (2006.01)

 (Continued)

(Continued)

(58) Field of Classification Search

CPC .. A61C 7/08; B32B 7/02; B32B 27/40; B32B 25/08; B32B 25/20; B32B 27/08;

(Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

2,467,432 A 4/1949 Kesling 3,407,500 A 10/1968 Kesling (Continued)

FOREIGN PATENT DOCUMENTS

AU 3031677 A 5/1979 AU 517102 B2 7/1981 (Continued)

OTHER PUBLICATIONS


AADR. American Association for Dental Research, Summary of Activities, Mar. 20-23, 1980, Los Angeles, CA, p. 195.

(Continued)

Primary Examiner — Jacob T Minskey
Assistant Examiner — Caroline Beha
(74) Attorney, Agent, or Firm — Wilson Sonsini Goodrich
& Rosati

(57) ABSTRACT

A dental appliance for positioning a patient's teeth includes a removable orthodontic tooth positioning appliance having teeth receiving cavities shaped to directly receive at least some of the patient's teeth and apply a resilient positioning force to the patient's teeth. The appliance includes a hard polymer layer having a hard polymer layer elastic modulus disposed between a first soft polymer layer having a first soft polymer layer elastic modulus and a second soft polymer layer having a second soft polymer layer elastic modulus. The hard polymer layer elastic modulus is greater than each of the first soft polymer layer elastic modulus and the second soft polymer layer elastic modulus. At least one of the first (Continued)



Page 2

soft polymer layer and the second soft polymer layer has a flexural modulus of greater than about 35,000 psi.

30 Claims, 8 Drawing Sheets

Related U.S. Application Data

(51) **Int. Cl.**

B32B 25/08

B32B 27/08

division of application No. 13/470,681, filed on May 14, 2012, now Pat. No. 9,655,691.

(2006.01)

(2006.01)

```
B32B 27/40
                           (2006.01)
     B32B 7/02
                           (2019.01)
     B29C 51/14
                           (2006.01)
      B29K 67/00
                           (2006.01)
     B29K 75/00
                           (2006.01)
     B32B 25/20
                           (2006.01)
     B32B 27/30
                           (2006.01)
     B32B 27/32
                           (2006.01)
     B32B 27/34
                           (2006.01)
     B32B 27/36
                           (2006.01)
     B29L 31/00
                           (2006.01)
     B32B 25/14
                           (2006.01)
     A61C 13/00
                           (2006.01)
     A61F 5/56
                           (2006.01)
     A61C 19/06
                           (2006.01)
     A61C 7/00
                           (2006.01)
     A63B 71/08
                          (2006.01)
(52) U.S. Cl.
     CPC ...... B32B 25/20 (2013.01); B32B 27/08
               (2013.01); B32B 27/281 (2013.01); B32B
              27/285 (2013.01); B32B 27/286 (2013.01);
                   B32B 27/308 (2013.01); B32B 27/32
          (2013.01); B32B 27/34 (2013.01); B32B 27/36
               (2013.01); B32B 27/365 (2013.01); B32B
           27/40 (2013.01); A61C 7/00 (2013.01); A61C
           13/00 (2013.01); A61C 19/06 (2013.01); A61F
           5/56 (2013.01); A63B 71/085 (2013.01); B29K
            2067/00 (2013.01); B29K 2075/00 (2013.01);
             B29K 2995/007 (2013.01); B29K 2995/0026
            (2013.01); B29K 2995/0077 (2013.01); B29K
                   2995/0082 (2013.01); B29L 2031/753
                 (2013.01); B32B 25/14 (2013.01); B32B
               27/283 (2013.01); B32B 27/30 (2013.01);
                 B32B 27/302 (2013.01); B32B 2250/03
              (2013.01); B32B 2250/24 (2013.01); B32B
            2250/40 (2013.01); B32B 2274/00 (2013.01);
               B32B 2307/40 (2013.01); B32B 2307/412
              (2013.01); B32B 2307/50 (2013.01); B32B
           2307/51 (2013.01); B32B 2307/536 (2013.01);
               B32B 2307/54 (2013.01); B32B 2307/546
              (2013.01); B32B 2319/00 (2013.01); B32B
            2323/00 (2013.01); B32B 2323/04 (2013.01);
                B32B 2323/10 (2013.01); B32B 2323/16
              (2013.01); B32B 2333/04 (2013.01); B32B
            2367/00 (2013.01); B32B 2371/00 (2013.01);
                B32B 2375/00 (2013.01); B32B 2377/00
              (2013.01); B32B 2383/00 (2013.01); B32B
            2535/00 (2013.01); B32B 2555/00 (2013.01);
            Y10T 428/31551 (2015.04); Y10T 428/31565
                   (2015.04); Y10T 428/31786 (2015.04)
```

(58) Field of Classification Search

CPC ... B32B 27/281; B32B 27/286; B32B 27/308; B32B 27/32; B32B 27/34; B32B 27/36; B32B 27/365; B32B 2250/24; B32B 2307/54; B32B 2250/03; B32B 2274/00; B32B 2307/412; B32B 2307/536; B32B 2535/00; B32B 2307/546; B29C 51/14; B29K 2995/007; B29K 2067/00; B29K 2075/00; B29K 2995/0026; B29K 2995/007; B29K 2995/0082; B29L 2031/753

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,600,808 A 8/1971 Reeve 3,660,900 A 5/1972 Andrews 3,683,502 8/1972 Wallshein 3,738,005 A 6/1973 Cohen et al 10/1973 3,763,109 A Witsiepe et al. 10/1973 3,766,146 A Witsiepe et al. 3,860,803 A 1/1975 Levine 3,916,526 A 11/1975 Schudy 3,922,786 A 12/1975 Lavin 3,950,851 A 4/1976 Bergersen 3,983,628 A 10/1976 Acevedo 4,014,096 A 3/1977 Dellinger 4,195,046 A 3/1980 Kesling et al. 3/1981 4.253.828 A Coles et al. 4,324,546 A 4/1982 Heitlinger et al. 4,324,547 A 4/1982 Arcan et al. 4,346,195 A 8/1982 Hornbaker et al. 4,348,178 A 9/1982 Kurz 4,410,595 A 10/1983 Matsumoto et al. 4,478,580 A 10/1984 Barrut et al. 4,500,294 A 2/1985 Lewis et al. 4.504.225 A 3/1985 Yoshii 4,505,673 A 3/1985 Yoshii et al. 4,526,540 A 7/1985 Dellinger et al. 4,575,330 A 3/1986 Hull et al. 4,575,805 A 3/1986 Moermann et al. 4,591,341 A 5/1986 Andrews et al. 4,609,349 A 9/1986 Cain et al 4.611.288 A 9/1986 Duret et al. 4,656,860 A 4,663,720 A 4/1987 Orthuber et al. 5/1987 Duret et al. 4,664,626 A 5/1987 Kesling et al. 4,676,747 6/1987 Kesling et al. 4,739,012 A 4/1988 Hagman 4,742,464 A 5/1988 Duret et al. 4,755,139 A 7/1988 Abbatte et al. 4,763,791 8/1988 Halverson et al. 4,791,156 A 12/1988 Hostettler 12/1988 4,793,803 A Martz 4,798,534 A 1/1989 Breads et al. 4,824,723 A 4/1989 Campbell et al. 4,836,778 A 6/1989 Baumrind et al. 4,837,732 A 6/1989 Brandestini et al. 4,843,124 A 6/1989 Wolfe, Jr. 4,850,864 A 7/1989 Diamond et al. 4.850.865 A 7/1989 Napolitano et al. 4,856,991 8/1989 Breads et al. 4,877,398 A 10/1989 Kesling et al. 4,880,380 A 11/1989 Martz et al. Batchelor et al. 4,889,238 A 12/1989 4,890,608 A 1/1990 Steer et al. 4,935,635 A 6/1990 O'Harra et al. 4,936,862 A 6/1990 Walker et al. 4,937,928 A 7/1990 van der Zel et al. 4,941,826 A 7/1990 Loran et al. 4,964,770 A 10/1990 Steinbichler et al. 4,975,052 A 12/1990 Spencer et al. 4,983,334 A 1/1991 Adell et al. 5,011,405 A 4/1991 Lemchen

US 11,154,384 B2 Page 3

(56)		Referen	ces Cited	6,049,743		4/2000	
	IIC	DATENT	DOCUMENTS	6,062,861 6,068,482			Andersson Snow et al.
	0.3.	PATENT	DOCUMENTS	6,099,314			Kopelman et al.
5,017	7,133 A	5/1991	Miura et al.	6,123,544		9/2000	
	1,790 A		Grossman et al.	6,152,731			Jordan et al. Chishti et al.
	7,281 A		Rekow et al. Breads et al.	6,183,248 6,190,165			Andreiko et al.
	5,613 A 5,039 A		Abbatte et al.	6,217,325			Chishti et al.
	9,118 A		Breads et al.	6,217,334			Hultgren et al.
5,100),316 A	3/1992	Wildman et al.	6,244,861			Andreiko et al.
,	1,333 A	6/1992	Riley et al.	6,309,215 6,315,553			Phan et al. Sachdeva et al.
	5,832 A 3,870 A	6/1992 7/1992	Erdman et al.	6,322,359			Jordan et al.
	0,064 A		Smalley et al.	6,350,120			Sachdeva et al.
	1,843 A		Hilgers et al.	6,382,975			Poirier et al. Chishti et al.
	1,844 A		Marinaccio et al. Andreiko et al.	6,390,812 6,398,548			Muhammad et al.
	9,419 A 5,364 A		Martz et al.	6,402,707			Ernst et al.
	5,517 A		Truax et al.	6,454,565			Phan et al.
	1,306 A		Erdman et al.	6,482,298 6,485,298		11/2002	Bhatnagar et al. Chishti et al.
	5,623 A 7,203 A		Breads et al. Riley et al.	6,524,101			Phan et al.
	3,429 A		Rekow et al.	6,554,611			Shishti et al.
	3,756 A		Lemchen et al.	6,572,372			Phan et al.
	3,362 A		Watson et al.	6,629,840 6,667,101			Chishti et al. Silagy et al.
	5,675 A 3,198 A		Wheeler et al. Wu et al.	6,705,861			Chishti et al.
,),309 A		Robertson et al.	6,705,863			Phan et al.
	2,202 A	8/1994	Deshayes et al.	6,722,880			Chishti et al.
	8,478 A 2,164 A		Andreiko et al. Stern et al.	6,746,757 7,121,825			Takagi et al. Chishti et al.
	5,238 A		Andreiko et al.	7,201,575	B2		Adell et al.
	1,562 A		Andreiko et al.	7,354,270			Abolfathi et al.
),326 A		Quinn et al.	7,641,828	B2 *	1/2010	DeSimone A61C 7/08 264/129
),496 A 7,432 A		Andersson et al. Andreiko et al.	8,235,713	В2	8/2012	Phan et al.
	2,219 A		Dehoff et al.	8,496,473	B2		Phan et al.
	1,717 A		Andreiko et al.	9,655,691			Li et al.
	5,600 A		Andreiko et al. Andreiko et al.	9,655,693 10,052,176			Li et al. Li et al.
	1,448 A 5,169 E		Lemchen et al.	10,492,888			Chen et al.
	3,397 A		Andreiko et al.	2001/0041320			Phan et al.
	3,735 A		Strasnick et al.	2002/0006597 2002/0146549			Andreiko et al. Kranenburg-Van Dijk et al.
	3,895 A 2,842 A		Andreiko et al. Andreiko et al.	2002/0140349			Phan et al.
	9,476 A		Stern et al.	2003/0009252			Pavlovskaia et al.
5,562	2,448 A		Mushabac	2003/0139834			Nikolskiy et al.
	7,912 A		Andersson et al.	2003/0190576 2003/0224311			Phan et al. Cronauer
	5,459 A 7,305 A		Kuroda et al. Andersson et al.	2004/0128010			Pavlovskaia et al.
	1,075 A		Andre, Sr. et al.	2004/0146670			Chin et al.
5,621	1,648 A		Crump et al.	2004/0170941 2005/0055118			Phan et al. Nikolskiy et al.
	5,420 A 5,421 A		Bergersen et al. Slootsky et al.	2005/0033118			Tadros et al.
	5,653 A		Chester et al.	2007/0087300		4/2007	Willison et al.
5,683	3,243 A		Andreiko et al.	2007/0148608			Tadros et al.
	2,894 A		Schwartz et al.	2007/0231765 2008/0020337			Phan et al. Phan et al.
5,725	5,376 A 5,378 A		Poirier et al. Wang et al.	2008/0230938			Grefenstein et al.
	3,126 A		Andersson et al.	2008/0248438			DeSimone et al.
),267 A		Echerer et al.	2008/0299507 2009/0087808			Li et al. Soo et al.
	2,700 A 9,100 A		Yoon et al. Clarke et al.	2009/008/808			Nassi et al.
),174 A		Andersson et al.	2009/0239188			Ting et al.
	3,778 A		Schmitt et al.	2009/0246724			Chen et al.
	8,115 A		Little et al.	2009/0298006 2009/0306327			Schwartz Stewart et al.
	7,853 A 5,058 A		van Nifterick et al. Batchelder et al.	2010/0055639			Lewis et al.
5,879	,158 A		Doyle et al.	2011/0020761	A1	1/2011	Kalili
5,880),961 A		Crump et al.	2011/0062609			Desimone et al.
),962 A 1,288 A	3/1999 8/1999	Andersson et al. Avila et al.	2011/0069134 2012/0315484			Sakagami et al. Riedl et al.
	1,288 A 7,686 A	9/1999	Anthony et al.	2012/0313484			Pudleiner et al.
	1,587 A	10/1999	Sato et al.	2015/0374464		12/2015	
5,971	1,754 A	10/1999	Sondhi et al.	2016/0228215	A1		Li et al.
	5,893 A	11/1999	Chishti et al.	2017/0202641			Li et al.
	5,289 A 1,309 A	1/2000 3/2000	Andreiko et al. Honda et al.	2019/0159870 2019/0183611			Li et al. Li et al.
0,044	1,505 1	5/2000	nonua et al.	2017/0103011	4 3 1	0/2019	Li St III.

Page 4

(56) References Cited

U.S. PATENT DOCUMENTS

2019/0231484 A	1 8/2019	Li et al.
2019/0286291 A	1 9/2019	Wen
2020/0290262 A	1 9/2020	Aguilar Mendez et al.
2020/0346449 A	1 11/2020	Li et al.

FOREIGN PATENT DOCUMENTS

ΑU	5598894 A	6/1994
CA	1121955 A	4/1982
CN	103374211 A	10/2013
DE	2749802 A1	5/1978
DE	69327661 T2	7/2000
DE	102004014023 A1	10/2005
DE	102010009230 A1	8/2011
DE	102010036107 A1	3/2012
DE	202013001392 U1	4/2013
EP	0091876 A1	10/1983
EP	0299490 A2	1/1989
EP	0376873 A2	7/1990
EP	0490848 A2	6/1992
EP	0541500 A1	5/1993
EP	0667753 B1	1/2000
EP		12/2000
EP	0731673 B1	5/2001
ES	463897 A1	1/1980
FR	2369828 A1	6/1978
FR	2652256 A1	3/1991
GB	1550777 A	8/1979
JP	S5358191 A	5/1978
JP	H0428359 A	1/1992
JP	H06256630 A	9/1994
JP	08508174	9/1996
JP	H08508174 A	9/1996
JP	2004099656 A	4/2004
JP	2011079284 A	4/2011
RU	2201944 C2	4/2003
RU	2008137623 A	3/2010
WO	WO-9008512 A1	8/1990
WO	WO-9104713 A1	4/1991
WO	WO-9410935 A1	5/1994
WO	WO-9711106 A1	3/1997
WO	WO-9832394 A1	7/1998
WO	WO-9844865 A1	10/1998
WO	WO-9858596 A1	12/1998
WO	WO-0180762 A2	11/2001
WO	WO-0180764 A1	11/2001
WO	WO-2004041898 A1	5/2004
WO	WO-2006096558 A2	9/2006
wo	WO-2010043419 A1	4/2010
wo	WO-2010043419 A1	7/2010
WO	WO-2010074789 A1 WO-2013172812 A1	11/2013
W	WO-20131/2012 AI	11/2013

OTHER PUBLICATIONS

Alcaniz, et al., "An Advanced System for the Simulation and Planning of Orthodontic Treatments," Karl Heinz Hohne and Ron Kikinis (eds.), Visualization in Biomedical Computing, 4th Intl. Conf., VBC '96, Hamburg, Germany, Sep. 22-25, 1996, Springer-Verlag, pp. 511-520.

Alexander et al., "The DigiGraph Work Station Part 2 Clinical Management," JCO, pp. 402-407 (Jul. 1990).

Altschuler, "3D Mapping of Maxillo-Facial Prosthesis," AADR Abstract #607, 2 pages total, (1980).

Altschuler et al., "Analysis of 3-D Data for Comparative 3-D Serial Growth Pattern Studies of Oral-Facial Structures," IADR Abstracts, Program and Abstracts of Papers, 57th General Session, IADR Annual Session, Mar. 29, 1979-Apr. 1, 1979, New Orleans Marriot, Journal of Dental Research, vol. 58, Jan. 1979, Special Issue A, p. 221.

Altschuler et al., "Laser Electro-Optic System for Rapid Three-Dimensional (3D) Topographic Mapping of Surfaces," Optical Engineering, 20(6):953-961 (1981).

Altschuler et al., "Measuring Surfaces Space-Coded by a Laser-Projected Dot Matrix," SPIE Imaging Applications for Automated Industrial Inspection and Assembly, vol. 182, p. 187-191 (1979). Andersson et al., "Clinical Results with Titanium Crowns Fabri-

cated with Machine Duplication and Spark Erosion," Acta. Odontol. Scand., 47:279-286 (1989).

Andrews, The Six Keys to Optimal Occlusion Straight Wire, Chapter 3, pp. 13-24 (1989).

Andrews, The Six Keys to Optimal Occlusion Straight Wire, Chapter 3, pp. 13-24 (No Date Given).

Baird Equity Research. Align Technology, Inc. (ALGN): Analyst Day Recap. May 30, 2014. 12 pages.

Baird Equity Research. Align Technology, Inc. (ALGN): Impressive Quarter/Guide, Momentum Stronger than We Realized. Oct. 18, 2013. 15 pages.

Bartels, et al., An Introduction to Splines for Use in Computer Graphics and Geometric Modeling, Morgan Kaufmann Publishers, pp. 422-425 (1987).

Baumrind, "A System for Craniofacial Mapping Through the Integration of Data from Stereo X-Ray Films and Stereo Photographs," an invited paper submitted to the 1975 American Society of Photogram Symposium on Close-Range Photogram Systems, University of III., Aug. 26-30, 1975, pp. 142-166.

Baumrind et al., "A Stereophotogrammetric System for the Detection of Prosthesis Loosening in Total Hip Arthroplasty," NATO Symposium on Applications of Human Biostereometrics, Jul. 9-13, 1978, SPIE, vol. 166, pp. 112-123.

Baumrind et al., "Mapping the Skull in 3-D," reprinted from J. Calif. Dent. Assoc., 48(2), 11 pages total, (1972 Fall Issue).

Baumrind, "Integrated Three-Dimensional Craniofacial Mapping: Background, Principles, and Perspectives," Semin. in Orthod., 7(4):223-232 (Dec. 2001).

Bayer Corporation, "TEXIN® 990R," pp. 1-4, Nov. 2002, Pittsburgh, PA.

Begole et al., "A Computer System for the Analysis of Dental Casts," The Angle Orthod., 51(3):253-259 (Jul. 1981).

Bernard et al., "Computerized Diagnosis in Orthodontics for Epidemiological Studies: A Progress Report," Abstract, J. Dental Res. Special Issue, vol. 67, p. 169, paper presented at International Association for Dental Research 66th General Session, Mar. 9-13, 1988, Montreal, Canada.

Bhatia et al., "A Computer-Aided Design for Orthognathic Surgery," Br. J. Oral Maxillofac. Surg., 22:237-253 (1984).

Biggerstaff, "Computerized Diagnostic Setups and Simulations," Angle Orthod., 40(1):28-36 (Jan. 1970).

Biggerstaff et al., "Computerized Analysis of Occlusion in the Postcanine Dentition," Am. J. Orthod., 61(3): 245-254 (Mar. 1972). Biostar Opeation & Training Manual. Great Lakes Orthodontics, Ltd. 199 Fire Tower Drive, Tonawanda, New York. 14150-5890, 20 pages total (1990).

Biostar Opeation & Training Manual. Great Lakes Orthodontics, Ltd. 199 Fire Tower Drive, Tonawanda, New York. 14150-5890, 20 pages total (No Date Given).

Blu, et al., "Linear interpolation revitalized", IEEE Trans. Image Proc., 13(5):710-719 (May 2004.

Boedeker.com. Polycarbonate specifications [retrieved on Sep. 10, 2013]. Retrieved from the Internet: http://www.boedeker.com/polyc_p.htm.

Bourke, "Coordinate System Transformation," (Jun. 1996), p. 1, retrieved from the Internet Nov. 5, 2004, URL http://astronomy.swin.edu.au/-pbourke/prolection/coords.

Boyd et al., "Three Dimensional Diagnosis and Orthodontic Treatment of Complex Malocclusions With the Invisalign Appliance," Semin. Orthod., 7(4):274-293 (Dec. 2001).

Brandestini et al., "Computer Machined Ceramic Inlays: In Vitro Marginal Adaptation," J. Dent. Res. Special Issue, Abstract 305, vol. 64, p. 208 (1985).

Brook et al., "An Image Analysis System for the Determination of Tooth Dimensions from Study Casts: Comparison with Manual Measurements of Mesio-distal Diameter," J. Dent. Res., 65(3):428-431 (Mar. 1986).

Page 5

(56) References Cited

OTHER PUBLICATIONS

Burstone et al., Precision Adjustment of the Transpalatal Lingual Arch: Computer Arch Form in Predetermination, Am, Journal of Orthodontics, vol. 79, No. 2 (Feb. 1981), pp. 115-133.

Burstone (interview), "Dr. Charles J. Burstone on the Uses of the Computer in Orthodontic Practice (Part 1)," J. Clin. Orthod., 13(7):442-453 (Jul. 1979).

Burstone (interview), "Dr. Charles J. Burstone on the Uses of the Computer in Orthodontic Practice (Part 2)," J. Clin. Orthod., 13(8):539-551 (Aug. 1979).

Campo, E. A. "Mechanical Properties of Polymeric Materials," from "Selection of Polymeric Materials: Plastics Design Library," 2008, 4 pages.

Cardinal Industrial Finishes, Powder Coatings information posted at http://www.cardinalpaint.com on Aug. 25, 2000, 2 pages.

Carnaghan, "An Alternative to Holograms for the Portrayal of Human Teeth," 4th Int'l. Conf. on Holographic Systems, Components and Applications, Sep. 15, 1993, pp. 228-231.

Chaconas et al., "The DigiGraph Work Station, Part 1, Basic Concepts," JCO, pp. 360-367 (Jun. 1990).

Chafetz et al., "Subsidence of the Femoral Prosthesis, A Stereophotogrammetric Evaluation," Clin. Orthop. Relat. Res., No. 201, pp. 60-67 (Dec. 1985).

Chiappone, (1980). Constructing the Gnathologic Setup and Positioner, J. Clin. Orthod, vol. 14, pp. 121-133.

Cottingham, (1969). Gnathologic Clear Plastic Positioner, Am. J. Orthod, vol. 55, pp. 23-31.

Crawford, "CAD/CAM in the Dental Office: Does It Work?", Canadian Dental Journal, vol. 57, No. 2, pp. 121-123 (Feb. 1991). Crawford, "Computers in Dentistry: Part 1 CAD/CAM: The Computer Moves Chairside," Part 2 F. Duret—A Man with a Vision, "Part 3 The Computer Gives New Vision—Literally," Part 4 Bytes 'N Bites—The Computer Moves from the Front Desk to the Operatory, Canadian Dental Journal, vol. 54 (9), pp. 661-666 (1988).

Canadian Dental Journal, vol. 54 (9), pp. 661-666 (1988). Crooks, "CAD/CAM Comes to USC," USC Dentistry, pp. 14-17 (Spring 1990).

Cureton, Correcting Malaligned Mandibular Incisors with Removable Retainers, J. Clin. Orthod, vol. 30, No. 7 (1996) pp. 390-395. Curry et al., "Integrated Three-Dimensional Craniofacial Mapping at the Craniofacial Research Instrumentation Laboratory/University of the Pacific," Semin. Orthod., 7(4):258-265 (Dec. 2001).

of the Pacific," Semin. Orthod., 7(4):258-265 (Dec. 2001). Cutting et a/., "Three-Dimensional Computer-Assisted Design of Craniofacial Surgical Procedures: Optimization and Interaction with Cephalometric and CT-Based Models," Plast. 77(6):877-885 (Jun. 1986).

DCS Dental AG, "The CAD/CAM 'DCS Titan System' for Production of Crowns/Bridges," DSC Production AG, pp. 1-7 (Jan. 1992

Definition for gingiva. Dictionary.com p. 1-3. Retrieved from the internet Nov. 5, 2004 http://reference.com/search/search?q=gingiva.

Defranco et al., "Three-Dimensional Large Displacement Analysis of Orthodontic Appliances," J. Biomechanics, 9:793-801 (1976).

Dental Institute University of Zurich Switzerland, Program for International Symposium JD on Computer Restorations: State of the Art of the CEREC-Method, May 1991, 2 pages total.

Dentrac Corporation, Dentrac document, pp. 4-13 (1992).

Dentrac Corporation, Dentrac document, pp. 4-13 (No Date Given). Dent-X posted on Sep. 24, 1998 at http://www.dent-x.com/DentSim.htm, 6 pages.

Doyle, "Digital Dentistry," Computer Graphics World, pp. 50-52, 54 (Oct. 2000).

DuraClearTM product information, Allesee Orthodontic Appliances-Pro Lab, 1 page (1997).

DuraClearTM product information, Allesee Orthodontic Appliances-Pro Lab, 1 page (No Date Given).

Duret et al., "CAD/CAM Imaging in Dentistry," Curr. Opin. Dent., 1:150-154 (1991).

Duret et al, "CAD-CAM in Dentistry," J. Am. Dent. Assoc. 117:715-720 (Nov. 1988).

Duret, "The Dental CAD/CAM, General Description of the Project," Hennson International Product Brochure, 18 pages total, Jan. 1986.

Duret, "Vers Une Prosthese Informatisee," (English translation attached), Tonus, vol. 75, pp. 55-57 (Nov. 15, 1985).

Economides, "The Microcomputer in the Orthodontic Office," JCO, pp. 767-772 (Nov. 1979).

Elsasser, Some Observations on the History and Uses of the Kesling Positioner, Am. J. Orthod. (1950) 36:368-374.

Emblem, A. "Plastics properties for packaging materials," from "Packaging Technology: Fundamentals, Materials and Processes," 2012, 3 pages.

English translation of Japanese Laid-Open Publication No. 63-11148 to inventor T. Ozukuri (Laid-Open on Jan. 18, 1998) pp. 1-7.

Felton et al., "A Computerized Analysis of the Shape and Stability of Mandibular Arch Form," Am. J. Orthod. Dentofacial Orthop., 92(6):478-483 (Dec. 1987).

Friede et al., "Accuracy of Cephalometric Prediction in Orthognathic Surgery," Abstract of Papers, J. Dent. Res., 70:754-760 (1987).

Futterling et al., "Automated Finite Element Modeling of a Human Mandible with Dental Implants," JS WSCG '98—Conference Program, retrieved from the Internet: http://wscg.zcu.cz/wscg98/papers98/Strasser 98.pdf, 8 pages.

Gao et al., "3-D element Generation for Multi-Connected Complex Dental and Mandibular Structure," Proc. Intl Workshop on Medical Imaging and Augmented Reality, pp. 267-271 (Jun. 12, 2001).

Gim-Alldent Deutschland, "Das DUX System: Die Technik," 2 pages total (2002).

Gottleib et al., "JCO Interviews Dr. James A. McNamura, Jr., on the Frankel Appliance: Part 2: Clinical 1-1 Management," J. Clin. Orthod., 16(6):390-407 (Jun. 1982).

Grayson, "New Methods for Three Dimensional Analysis of Craniofacial Deformity, Symposium: JW Computerized Facial Imaging in Oral and Maxillofacial Surgery," AAOMS, 3 pages total, (Sep. 13, 1990). Guess et al., "Computer Treatment Estimates in Orthodontics and Orthognathic Surgery," JCO, pp. 262-28 (Apr. 1989).

Heaven et al., "Computer-Based Image Analysis of Artificial Root Surface Caries," Abstracts of Papers, J. Dent. Res., 70:528 (Apr. 17-21, 1991).

Highbeam Research, "Simulating Stress Put on Jaw," Tooling & Production [online], Nov. 1996, n pp. 1-2, retrieved from the Internet on Nov. 5, 2004, URL http://static.highbeam.com/t/toolingampproduction/november011996/simulatingstressputonfa...

Hikage, "Integrated Orthodontic Management System for Virtual Three-Dimensional Computer Graphic Simulation and Optical Video Image Database for Diagnosis and Treatment Planning", Journal of Japan KA Orthodontic Society, Feb. 1987, English translation, pp. 1-38, Japanese version, 46(2), pp. 248-269 (60 pages total).

Hoffmann, et al., "Role of Cephalometry for Planning of Jaw Orthopedics and Jaw Surgery Procedures," (Article Summary in English, article in German), Informationen, pp. 375-396 (Mar. 1991).

Hojjatie et al., "Three-Dimensional Finite Element Analysis of Glass-Ceramic Dental Crowns," J. Biomech., 23(11):1157-1166 (1990).

Huckins, "CAD-CAM Generated Mandibular Model Prototype from MRI Data," AAOMS, p. 96 (1999).

Important Tip About Wearing the Red White & Blue Active Clear Retainer System. Allesee Orthodontic Appliances-Pro Lab. 1 page (1998)

International Preliminary Report on Patentability dated Nov. 18, 2014 for International PCT Patent Application No. PCT/US2012/037745.

International Search Report and Written Opinion dated Jan. 30, 2013 for International PCT Patent Application No. PCT/US2012/037745.

International search report with written opinion dated Jun. 28, 2013 for PCT/EP2013/059701.

JCO Interviews, "Craig Andreiko, DDS, MS on the Elan and Orthos Systems," JCO, pp. 459-468 (Aug. 1994).

JCO Interviews, "Dr. Homer W. Phillips on Computers in Orthodontic Practice, Part 2," JCO. 1997; 1983:819-831.

Page 6

(56) References Cited

OTHER PUBLICATIONS

Jerrold, "The Problem, Electronic Data Transmission and the Law," AJO-DO, pp. 478-479 (Apr. 1988).

Jones et al., "An Assessment of the Fit of a Parabolic Curve to Preand Post-Treatment Dental Arches," Br. J. Orthod., 16:85-93 (1989). JP Faber et al., "Computerized Interactive Orthodontic Treatment Planning," Am. J. Orthod., 73(1):36-46 (Jan. 1978).

Kamada et.al., Case Reports on Tooth Positioners Using LTV Vinyl Silicone Rubber, J. Nihon University School of Dentistry (1984) 26(1): 11-29.

Kamada et.al., Construction of Tooth Positioners with LTV Vinyl Silicone Rubber and Some Case KJ Reports, J. Nihon University School of Dentistry (1982) 24(1):1-27.

Kanazawa et al., "Three-Dimensional Measurements of the Occlusal Surfaces of Upper Molars in a Dutch Population," J. Dent Res., 63(11):1298-1301 (Nov. 1984).

Kesling, Coordinating the Predetermined Pattern and Tooth Positioner with Conventional Treatment, KN Am. J. Orthod. Oral Surg. (1946) 32:285-293.

Kesling et al., The Philosophy of the Tooth Positioning Appliance, American Journal of Orthodontics and Oral surgery. 1945; 31:297-304.

Kleeman et al., The Speed Positioner, J. Clin. Orthod. (1996) 30:673-680.

Kochanek, "Interpolating Splines with Local Tension, Continuity and Bias Control," Computer Graphics, ri 18(3):33-41 (Jul. 1984). KM Oral Surgery (1945) 31:297-30.

Kunii et al., "Articulation Simulation for an Intelligent Dental Care System," Displays 15:181-188 (1994).

Kuroda et al., Three-Dimensional Dental Cast Analyzing System Using Laser Scanning, Am. J. Orthod. Dentofac. Orthop. (1996) 110:365-369.

Larson, Kent "Can You Estimate Modulus From Durometer Hardness for Silicones?" Dow White Paper, 2019 The Dow Chemical Company, Form No. 11-3716-01A S2D, pp. 1-5.

Laurendeau, et al., "A Computer-Vision Technique for the Acquisition and Processing of 3-D Profiles of 7 KR Dental Imprints: An Application in Orthodontics," IEEE Transactions on Medical Imaging, 10(3):453-461 (Sep. 1991.

Leinfelder, et al., "A New Method for Generating Ceramic Restorations: a CAD-CAM System," J. Am. 1-1 Dent. Assoc., 118(6):703-707 (Jun. 1989).

Lubrizol.com. I sop last 2530 data sheet [retrieved on Sep. 10, 2013]. Retrieved from the Internet: http://www.lubrizol.com/Medicai/TDS/Isoplast-2530.pdf.

Manetti, et al., "Computer-Aided Cefalometry and New Mechanics in Orthodontics," (Article Summary in English, article in German), Fortschr Kieferorthop. 44, 370-376 (Nr. 5), 1983.

Material Data Sheet of Ecdel 9966. 3 pages total (Year: 2020).

McCann, "Inside the ADA," J. Amer. Dent. Assoc., 118:286-294 (Mar. 1989).

McNamara et al., "Invisible Retainers," J. Clin. Orthod., pp. 570-578 (Aug. 1985).

McNamara et al., Orthodontic and Orthopedic Treatment in the Mixed Dentition, Needham Press, pp. 347-353 (Jan. 1993).

Moermann et al., "Computer Machined Adhesive Porcelain Inlays: Margin Adaptation after Fatigue Stress," IADR Abstract 339, J. Dent. Res., 66(a):763 (1987).

Moles, "Correcting Mild Malalignments—As Easy As One, Two, Three," AOA/Pro Corner, vol. 11, No. 1, 2 pages (2002).

Mormann et al., "Marginale Adaptation von adhasuven Porzellaninlays in vitro," Separatdruck aus: Schweiz. Mschr. Zahnmed. 95: 1118-1129, 1985.

Nahoum, "The Vacuum Formed Dental Contour Appliance," N. Y. State Dent. J., 30(9):385-390 (Nov. 1964).

Nash, "CEREC CAD/CAM Inlays: Aesthetics and Durability in a Single Appointment," Dent. Today, 9(8):20, 22-23 (Oct. 1990).

Nishiyama et al., "A New Construction of Tooth Repositioner by LTV Vinyl Silicone Rubber," J. Nihon Univ. Sch. Dent., 19(2):93-102 (1977).

"Overview of Materials for PETG Copolyester" 2 pages (http://www.nnatweb.conn/search/DataSheet.aspx?MatGUID= 4de1c85bb946406a86c52b688e3810d0&ckck=1) (webpage retrieved on Oct. 27, 2020) (Year: 2020).

Paul et al., "Digital Documentation of Individual Human Jaw and Tooth Forms for Applications in Orthodontics, Oral Surgery and Forensic Medicine" Proc. of the 24th Annual Conf. of the IEEE Industrial Electronics Society (IECON '98), Sep. 4, 1998, pp. 2415-2418.

Pinkham, "Foolish Concept Propels Technology," Dentist, 3 pages total, Jan./Feb. 1989.

Pinkham, "Inventor's CAD/CAM May Transform Dentistry," Dentist, 3 pages total, Sep. 1990.

Plastics.ides.com. Polyurethane Thermoset Elastomer Typical Properties Generic [retrieved on Jul. 27, 2014]. Retrieved from the Internet: http://plastics.ides.com/generics/57/c/t/polyurethane-thermoset-elastomer-tsu-properties-processing.

"Polycarbonate," Encyclopaedia Britannica, Aug. 24, 2017, 1 page, URL: https://www.britannica.com/science/polycarbonate.

Ponitz, "Invisible Retainers," Am. J. Orthod., 59(3):266-272 (Mar. 1971).

Procera Research Projects, "PROCERA Research Projects 1993—Abstract Collection," pp. 3-7; 28 (1993).

Proffit et al., Contemporary Orthodontics, (Second Ed.), Chapter 15, Mosby Inc., pp. 470-533 (Oct. 1993.

Raintree Essix & ARS Materials, Inc., Raintree Essix, Technical Magazine Table of contents and Essix Appliances, http://www.essix.com/magazine/defaulthtml Aug. 13, 1997.

Redmond et al., "Clinical Implications of Digital Orthodontics," Am. J. Orthod. Dentofacial Orthop., 117(2):240-242 (2000).

Rekow, "A Review of the Developments in Dental CAD/CAM Systems," (contains references to Japanese efforts and content of the papers of particular interest to the clinician are indicated with a one line summary of their content in the bibliography), Curr. Opin. Dent., 2:25-33 (Jun. 1992).

Rekow, "CAD/CAM in Dentistry: A Historical Perspective and View of the Future," J. Can. Dent. Assoc., 58(4):283, 287-288 (Apr. 1992)

Rekow, "Computer-Aided Design and Manufacturing in Dentistry: A Review of the State of the Art," J. Prosthet. Dent., 58(4):512-516 (Oct. 1987).

Rekow, "Dental CAD-CAM Systems: What is the State of the Art'?", J. Amer. Dent. Assoc., 122:43-48 1991.

Rekow et al., "CAD/CAM for Dental Restorations—Some of the Curious Challenges," IEEE Trans. Biomed. Eng., 38(4):314-318 (Apr. 1991).

Rekow et al., "Comparison of Three Data Acquisition Techniques for 3-D Tooth Surface Mapping," Annual International Conference of the IEEE Engineering in Medicine and Biology Society, 13(1):344-345 1991.

Rekow, "Feasibility of an Automated System for Production of Dental Restorations, Ph.D. Thesis," Univ. of Minnesota, 244 pages total, Nov. 1988.

Richmond et al., "The Development of a 3D Cast Analysis System," Br. J. Orthod., 13(1):53-54 (Jan. 1986).

Richmond et al., "The Development of the PAR Index (Peer Assessment Rating): Reliability and Validity," Eur. J. Orthod., 14:125-139 (1992).

Richmond, "Recording the Dental Cast in Three Dimensions," Am. J. Orthod. Dentofacial Orthop., 92(3):199-206 (Sep. 1987).

Rudge, "Dental Arch Analysis: Arch Form, A Review of the Literature," Eur. J. Orthod., 3(4):279-284 1981.

Sakuda et al., "Integrated Information-Processing System in Clinical Orthodontics: An Approach with Use of a Computer Network System," Am. J. Orthod. Dentofacial Orthop., 101(3): 210-220 (Mar. 1992).

Schellhas et al., "Three-Dimensional Computed Tomography in Maxillofacial Surgical Planning," Arch. Otolaryngol Head Neck Surg., 114:438-442 (Apr. 1988).

Schroeder et al., Eds. The Visual Toolkit, Prentice Hall PTR, New Jersey (1998) Chapters 6, 8 & 9, (pp. 153-210,309-354, and 355-428, respectively.

Page 7

(56) References Cited

OTHER PUBLICATIONS

Shilliday, (1971). Minimizing finishing problems with the minipositioner, Am. J. Orthod. 59:596-599.

Siemens, "CEREC—Computer-Reconstruction," High Tech in der Zahnmedizin, 14 pages total (2004).

Siemens, "CEREC—Computer-Reconstruction," High Tech in der Zahnmedizin, 14 pages total (No Date Given).

Sinclair, "The Readers' Corner," J. Clin. Orthod., 26(6):369-372 (Jun. 1992).

Sirona Dental Systems GmbH, CEREC 3D, Manuel utilisateur, Version 2.0X (in French), 2003,114 pages total.

Stifel. TAM Survey. Properly Aligning Expectations Ahead of 4Q13 Guidance. Align Technology, Inc. Oct. 10, 2013. 12 pages.

Stoll et al., "Computer-aided Technologies in Dentistry," (article summary in English, article in German), Dtsch Zahna'rztl Z 45, pp. 314-322 (1990).

Sturman, "Interactive Keyframe Animation of 3-D Articulated Models," Proceedings Graphics Interface '84, May-Jun. 1984, pp. 35-40

The Choice Is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee Orthodontic Appliances-Pro Lab product information, 6 pages (2003).

The Choice Is Clear: Red, White & Blue... The Simple, Affordable, No-Braces Treatment, Allesee HI Orthodontic Appliances-Pro Lab product information for doctors. http://ormco.com/aoa/appliancesservices/RWB/doctorhtml, 5 pages (May 19, 2003).

The Choice is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee HJ Orthodontic Appliances-Pro Lab product information for patients, (http://ormco.com/aoa/appliancesservices/RWB/patients.html), 2 pages (May 19, 2003).

The Red, White & Blue Way to Improve Your Smile!, Allesee Orthodontic Appliances-Pro Lab product information for patients, 2 pages (1992).

Truax L., "Truax Clasp-Less(TM) Appliance System," Funct. Orthod., 9(5):22-4, 26-8 (Sep.-Oct. 1992).

Tru-Tain Orthodontic & Dental Supplies, Product Brochure, Rochester, Minnesota 55902, 16 pages total (1996).

Tru-Tain Orthodontic & Dental Supplies, Product Brochure, Rochester, Minnesota 55902, 16 pages total (No Date Given).

U.S. Department of Commerce, National Technical Information Service, "Automated Crown Replication Using Solid Photography SM," Solid Photography Inc., Melville NY, Oct. 1977, 20 pages total.

U.S. Department of Commerce, National Technical Information Service, "Holodontography: An Introduction to Dental Laser Holography," School of Aerospace Medicine Brooks AFB Tex, Mar. 1973, 37 pages total.

U.S. Appl. No. 60/050,342, filed Jun. 20, 1997, 41 pages total. Van Der Linden, "A New Method to Determine Tooth Positions and Dental Arch Dimensions," J. Dent. Res., 51(4):1104 (Jul.-Aug. 1972).

Van Der Linden et al., "Three-Dimensional Analysis of Dental Casts by Means of the Optocom," J. Dent. Res., p. 1100 (Jul.-Aug. 1972). Van Der Zel, "Ceramic-Fused-to-Metal Restorations with a New CAD/CAM System," Quintessence Int., 24(11):769-778 (1993. Varady et al., "Reverse Engineering of Geometric Models—An Introduction," Computer-Aided Design, 29(4):255-268,1997.

Verstreken et al., "An Image-Guided Planning System for Endosseous Oral Implants," IEEE Trans. Med. Imaging, 17(5):842-852 (Oct. 1998).

Page 8 of 22

Warunek et al., Physical and Mechanical Properties of Elastomers in Orthodonic Positioners, Am J. Orthod. Dentofac. Orthop, vol. 95, No. 5, (May 1989) pp. 388-400.

Warunek et.al., Clinical Use of Silicone Elastomer Applicances, JCO (1989) XXIII(10):694-700.

Wells, Application of the Positioner Appliance in Orthodontic Treatment, Am. J. Orthodont. (1970) 58:351-366.

Williams, "Dentistry and CAD/CAM: Another French Revolution," J. Dent. Practice Admin., pp. 2-5 (Jan./Mar. 1987).

Williams, "The Switzerland and Minnesota Developments in CAD/CAM," J. Dent. Practice Admin., pp. 50-55 (Apr./Jun. 1987).

Wishan, "New Advances in Personal Computer Applications for Cephalometric Analysis, Growth Prediction, Surgical Treatment Planning and Imaging Processing," Symposium: Computerized Facial Imaging in Oral and Maxilofacial Surgery Presented on Sep. 13, 1999.

WSCG'98—Conference Program, "The Sixth International Conference in Central Europe on Computer Graphics and Visualization '98," Feb. 9-13, 1998, pp. 1-7, retrieved from the Internet on Nov. 5, 2004, URL(http://wscg.zcu.cz/wscg98/wscg98.h).

Xia et al., "Three-Dimensional Virtual-Reality Surgical Planning and Soft-Tissue Prediction for Orthognathic Surgery," IEEE Trans. Inf. Technol. Biomed., 5(2):97-107 (Jun. 2001).

Yamamoto et al., "Optical Measurement of Dental Cast Profile and Application to Analysis of Three-Dimensional Tooth Movement in Orthodontics," Front. Med. Biol. Eng., 1(2):119-130 (1988).

Yamamoto et al., "Three-Dimensional Measurement of Dental Cast Profiles and Its Applications to Orthodontics," Conf. Proc. IEEE Eng. Med. Biol. Soc., 12(5):2051-2053 (1990).

Yamany et al., "A System for Human Jaw Modeling Using Intra-Oral Images," Proc. of the 20th Annual Conf. of the IEEE Engineering in Medicine and Biology Society, Nov. 1, 1998, vol. 2, pp. 563-566.

Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); I. The D.P. Concept and Implementation of Transparent Silicone Resin (Orthocon)," Nippon Dental Review, 452:61-74 (Jun. 1980).

Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); II. The D.P. Manufacturing Procedure and Clinical Applications," Nippon Dental Review, 454:107-130 (Aug. 1980). Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); III. The General Concept of the D.P. Method and Its Therapeutic Effect, Part 1, Dental and Functional Reversed Occlusion Case Reports," Nippon Dental Review, 457:146-164 (Nov. 1980)

Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); III.—The General Concept of the D.P. Method and Its Therapeutic Effect, Part 2. Skeletal Reversed Occlusion Case Reports," Nippon Dental Review, 458:112-129 (Dec. 1980).

You May Be a Candidate for This Invisible No-Braces Treatment, Allesee Orthodontic Appliances-Pro Lab product information for patients, 2 pages (2002).

You May Be a Candidate for This Invisible No-Braces Treatment, Allesee Orthodontic Appliances-Pro Lab product information for patients, 2 pages (No Date Given).

* cited by examiner

U.S. Patent Oct. 26, 2021 Sheet 1 of 8 US 11,154,384 B2





FIG. 1

U.S. Patent Oct. 26, 2021 Sheet 2 of 8 US 11,154,384 B2



U.S. Patent Oct. 26, 2021 Sheet 3 of 8 US 11,154,384 B2




FIG. 3

U.S. Patent Oct. 26, 2021 Sheet 4 of 8 US 11,154,384 B2




FIG. 4

U.S. Patent

Oct. 26, 2021

Sheet 5 of 8

US 11,154,384 B2




FIG. 5

U.S. Patent Oct. 26, 2021 Sheet 6 of 8 US 11,154,384 B2




FIG. 6

U.S. Patent Oct. 26, 2021 Sheet 7 of 8 US 11,154,384 B2




FIG. 7

U.S. Patent Oct. 26, 2021 Sheet 8 of 8 US 11,154,384 B2




FIG. 8

1

MULTILAYER DENTAL APPLIANCES AND RELATED METHODS AND SYSTEMS

CROSS-REFERENCE

This application is a continuation of U.S. patent application Ser. No. 15/476,655, filed Mar. 31, 2017, which is a divisional of U.S. patent application Ser. No. 13/470,681, filed May 14, 2012, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention generally relates to the field of orthodontics, and more particularly to the design of multi- 15 layer dental positioning appliances.

An objective of orthodontics is to move a patient's teeth to positions where function and/or aesthetics are optimized. Traditionally, appliances such as braces are applied to a patient's teeth by a treating practitioner and the set of braces 20 exerts continual force on the teeth and gradually urges them toward their intended positions. Over time and with a series of clinical visits and reactive adjustments to the braces by the practitioner, the appliances to move the teeth toward their final destination.

More recently, alternatives to conventional orthodontic treatment with traditional affixed appliances (e.g., braces) have become available. For example, systems including a series of preformed appliances/aligners have become commercially available from Align Technology, Inc., San Jose, 30 Calif., under the trade name Invisalign® System. The Invisalign® System is described in numerous patents and patent applications assigned to Align Technology, Inc. including, for example in U.S. Pat. Nos. 6,450,807, and 5,975,893, as well as on the company's website, which is accessible on the 35 World Wide Web (see, e.g., the url invisalign.com"). The Invisalign® System includes designing and/or fabricating multiple, and sometimes all, of the aligners to be worn by the patient before the aligners are administered to the patient and used to reposition the teeth (e.g., at the outset of 40 treatment). Often, designing and planning a customized treatment for a patient makes use of computer-based 3-dimensional planning/design tools, such as $Treat^{TM}$ software from Align Technology, Inc. The design of the aligners relies on computer modeling of the patient's teeth in a series of 45 planned successive tooth arrangements, and the individual aligners are designed to be worn over the teeth, such that each aligner exerts force on the teeth and elastically repositions the teeth to each of the planned tooth arrangements.

While recently developed orthodontic treatment technologies, such as those described above, represent a considerable advancement in the field of orthodontics, additional advancements remain of interest. For example, in some instances it may be advantageous to develop materials that improve properties of the appliances/aligners used for orthodontic treatment. As such, there is a need for shell aligners that can, for example, produce more continuous force and better bring a patient's teeth into a desired occlusion.

BRIEF SUMMARY OF THE INVENTION

60

The present invention provides multilayer orthodontic positioning appliances, as well as related methods and systems. The disclosed multilayer appliances include a removable orthodontic tooth positioning appliance having 65 teeth receiving cavities shaped to directly receive at least some of the patient's teeth and apply a resilient positioning

2

force to the patient's teeth. The multilayer appliances can include a hard polymer layer disposed between two soft polymer layers. The multilayer dental appliances of the present invention, among many aspects, provide, for example, improved material performance, stress relaxation properties and longer working range. In addition, the mechanical properties of the materials and appliances described herein can improve orthodontic treatments by, for example, reducing the need for midcourse corrections during treatment and the number of aligners used for a given treatment.

The disclosed methods include methods for making multilayer dental appliances. The disclosed systems including a plurality of appliances having teeth receiving cavities shaped to directly receive at least some of the patient's teeth and apply a resilient positioning force to the patient's teeth. The appliances can be successively worn by a patient to move teeth from one arrangement to a successive arrangement. At least one of the appliances in the system can include a hard polymer layer disposed between two soft polymer layers.

For a fuller understanding of the nature and advantages of the present invention, reference should be made to the ensuing detailed description and accompanying drawings. Other aspects, objects and advantages of the invention will be apparent from the drawings and detailed description that follows

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a jaw and an incremental positioning appliance for the jaw, in accordance with an embodiment of the present invention.

FIG. 2 shows an arrangement of polymer layers in a sheet having a hard polymer layer disposed between two soft polymer layers, in accordance with an embodiment of the present invention.

FIG. 3 depicts a method of making a multilayer dental appliance, in accordance with an embodiment of the present invention.

FIG. 4 is a simplified block diagram illustrating a method for fabricating a dental appliance, in accordance with an embodiment of the present invention.

FIG. 5 provides a stress relaxation comparison for dental appliances, in accordance with an embodiment of the present invention.

FIG. 6 provides another stress relaxation comparison for dental appliances, in accordance with an embodiment of the present invention.

FIG. 7 shows a long-term unloading comparison for dental appliances, in accordance with an embodiment of the present invention.

FIG. **8** provides a long-term movement comparison for dental appliances, in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following description, various embodiments of the present invention will be described. For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the embodiments. However, it will also be apparent to one skilled in the art that the present invention may be practiced without the

3

specific details. Furthermore, well-known features may be omitted or simplified in order not to obscure the embodiment being described.

Multilayer orthodontic positioning appliances are provided, as well as related methods and systems. During 5 orthodontic treatment, it may be necessary to apply forces to a tooth to generate movement of the tooth to, for example, bring the patient's teeth into a better occlusion in a mesial or distal direction. The presently disclosed appliances, methods, and systems provide means by which such forces can be 10 applied during orthodontic treatment where appliances having teeth receiving cavities are used, such as preformed appliances/aligners available from Align Technology, Inc., San Jose, Calif., under the trade name Invisalign® System. As provided by the present invention, the aligners that 15 include multilayer sheets can, for example, provide increased durability of the aligners so that they can better withstand wear due to aligner reinsertion and removal and other mechanical stresses put on the aligner during treatment. In addition, the aligners have improved elastic prop- 20 erties that allow for less degradation in the shape of the teeth receiving cavities during a stage of treatment. For example, during a multistage orthodontic treatment, the force exerted by an aligner to perform defined tooth movement can degrade and may cause the treatment to include more 25 aligners to reach a final ideal arrangement and/or result in a mid-course correction that could be prevented by using aligners with improved physical properties, such as those provided herein.

In one embodiment, the present invention provides a 30 dental appliance for positioning a patient's teeth. The dental appliance can include a removable orthodontic tooth positioning appliance having teeth receiving cavities shaped to directly receive at least some of the patient's teeth and apply a resilient positioning force to the patient's teeth, the appliance comprising a hard polymer layer disposed between a first soft polymer layer and a second soft polymer layer.

In another embodiment, the present invention provides an orthodontic system for positioning a patient's teeth. The orthodontic system can include a plurality of incremental 40 position adjustment appliances having teeth receiving cavities shaped to directly receive at least some of the patient's teeth and apply a resilient positioning force to the patient's teeth, wherein the appliances are successively worn by a patient to move teeth from one arrangement to a successive 45 arrangement, and wherein at least one of the appliances comprises a hard polymer layer disposed between a first soft polymer layer and a second soft polymer layer.

In yet another embodiment, the present invention provides a method of making a dental appliance for positioning 50 a patient's teeth. The method can include providing a sheet comprising a hard polymer layer of polymeric material disposed between a first soft polymer layer and a second soft polymer layer, providing a positive model of the patient's teeth in a target position; and fabricating an appliance as a 55 negative of the positive model comprising thermoforming the sheet over the positive model.

Referring now to the drawings, in which like reference numerals represent like parts throughout the several views, FIG. 1 provides an appropriate starting point in a detailed 60 discussion of various embodiments of the present invention with respect to tooth repositioning appliances designed to apply repositioning forces to teeth. A tooth repositioning appliance 10 can be worn by a patient in order to achieve an incremental repositioning of individual teeth in the jaw 12. 65 The appliance can include a shell (e.g., a polymeric shell) having teeth-receiving cavities that receive and resiliently

4

reposition the teeth. In many embodiments, a polymeric appliance can be formed from a sheet of suitable layers of polymeric material. An appliance can fit over all teeth present in an upper or lower jaw, or less than all of the teeth. In some cases, only certain teeth received by an appliance will be repositioned by the appliance while other teeth can provide a base or anchor region for holding the appliance in place as it applies force against the tooth or teeth targeted for repositioning. In some cases, many or most, and even all, of the teeth will be repositioned at some point during treatment. Teeth that are moved can also serve as a base or anchor for holding the appliance as it is worn by the patient. Typically, no wires or other means will be provided for holding an appliance in place over the teeth. In some cases, however, it may be desirable or necessary to provide individual anchors on teeth with corresponding receptacles or apertures in the appliance so that the appliance can apply a selected force on the tooth. Exemplary appliances, including those utilized in the Invisalign® System, are described in numerous patents and patent applications assigned to Align Technology, Inc. including, for example, in U.S. Pat. Nos. 6,450,807, and 5,975,893, as well as on the company's website, which is accessible on the World Wide Web (see, e.g., the url invisalign.com").

An appliance can be designed and/or provided as part of a set of a plurality of appliances. In such an embodiment, each appliance may be configured so a tooth-receiving cavity has a geometry corresponding to an intermediate or final tooth arrangement intended for the appliance. The patient's teeth can be progressively repositioned from an initial tooth arrangement to a target tooth arrangement by placing a series of incremental position adjustment appliances over the patient's teeth. A target tooth arrangement can be a planned final tooth arrangement selected for the patient's teeth at the end of all planned orthodontic treatment. Alternatively, a target arrangement can be one of many intermediate arrangements for the patient's teeth during the course of orthodontic treatment, which may include where surgery is recommended, where inter-proximal reduction (IPR) is appropriate, where a progress check is scheduled, where anchor placement is best, where palatal expansion is desirable, etc. As such, it is understood that a target tooth arrangement can be any planned resulting arrangement for the patient's teeth that follows one or more incremental repositioning stages. Likewise, an initial tooth arrangement can be any initial arrangement for the patient's teeth that is followed by one or more incremental repositioning stages. The adjustment appliances can be generated all at the same stage or in sets or batches, e.g., at the beginning of a stage of the treatment, and the patient wears each appliance until the pressure of each appliance on the teeth can no longer be felt or has resulted in the maximum amount of expressed tooth movement for that given stage. A plurality of different appliances (e.g., set) can be designed and even fabricated prior to the patient wearing any appliance of the plurality. After wearing an appliance for an appropriate period of time, the patient replaces the current appliance with the next appliance in the series until no more appliances remain. The appliances are generally not affixed to the teeth and the patient may place and replace the appliances at any time during the procedure (e.g., patient-removable appliances). The final appliance or several appliances in the series may have a geometry or geometries selected to overcorrect the tooth arrangement, i.e., have a geometry which would (if fully achieved) move individual teeth beyond the tooth arrangement which has been selected as the "final." Such over-correction may be desirable in order to offset potential

Document 1-2

5

relapse after the repositioning method has been terminated, i.e., to permit movement of individual teeth back toward their pre-corrected positions. Over-correction may also be beneficial to speed the rate of correction, i.e., by having an appliance with a geometry that is positioned beyond a 5 desired intermediate or final position, the individual teeth will be shifted toward the position at a greater rate. In such cases, the use of an appliance can be terminated before the teeth reach the positions defined by the appliance.

In general, structures, methods and systems of the present 10 invention utilize a multilayer sheet for use in orthodontic appliances. The multilayer sheet can include three layers, in which a hard polymer layer is disposed between two soft polymer layers. The multilayer sheets used in the present invention can be used in making dental aligners having 15 improved durability for use, e.g., to the elastic properties of the multilayer sheet when formed into an aligner. In addition, the bonding strength between the layers further improves the durability of the aligners, for example, by withstanding teeth grinding by a patient.

FIG. 2 shows a multilayer structure according to the present invention. As shown, a multilayer sheet 20 can include a three layer structure: a hard polymer layer 24 and two soft polymer layers 22, 26. The hard polymer layer can be disposed between a first soft polymer layer and a second 25 soft polymer layer. In some embodiments, the hard polymer layer can be thicker than either of the soft polymer layers. The soft polymer layers can have the same or different thicknesses. For example, the hard polymer layer can range from a thickness of about 550 □m to about 750 □m. The 30 soft polymer layers can range from a thickness of about 25 ☐m to about 100 ☐m. Multilayer sheets used for making appliances having a hard polymer layer disposed between two soft polymer layers can range from a thickness of about 600 □m to about 1000 □m. In some embodiments, the 35 thicknesses of the various layers can be tailored for a particular stage of treatment for the patient.

Suitable polymeric materials for the hard polymer layer can include a polyester, a co-polyester, a polycarbonate, a thermoplastic polyurethane, a polypropylene, a polyethyl- 40 ene, a polypropylene and polyethylene copolymer, an acrylic, a cyclic block copolymer, a polyetheretherketone, a polyamide, a polyethylene terephthalate, a polybutylene terephthalate, a polyetherimide, a polyethersulfone, a polytrimethylene terephthalate or a combination thereof (e.g., a 45 blend of at least two of the listed hard polymeric materials). In some embodiments, the hard polymer layer of the appliances can include polymeric materials, such as a polycarbonate, a co-polyester, a polyester, and a thermoplastic polyurethane. In some embodiments, the hard layer can be 50 composed of multiple hard layers, e.g., two or three hard polymer layers 24-1, 24-2, 24-N co-extruded to form one

The hard polymer layer of the appliances of the present invention can have a variety of physical properties that can, 55 e.g., improve treatment options for a practitioner. For example, physical properties such as tensile strength, elongation at yield, elongation at break, tensile modulus, flexural modulus, stress relaxation over time, and light transmission can each be specifically tailored for a particular application. 60 In some embodiments, the hard polymer layer of the appliances can have a physical property of at least one of a tensile strength at yield of between about 4000 pounds per square inch (psi) and 6500 psi, an elongation at yield of greater than about 4%, an elongation at break of greater than about 70%, 65 a tensile modulus of greater than about 150,000 psi, a flexural modulus greater than about 150,000 psi, a stress

relaxation at 24 hours testing in a wet environment (e.g., between about 90%-100% relative humidity) is greater than 10%, and a light transmission between 400 nm and 800 nm of greater than about 75%.

Suitable polymeric materials for the soft polymer layers of the appliance can include a styrenic block copolymer (SBC), a silicone rubber, an elastomeric alloy, a thermoplastic elastomer (TPE), a thermoplastic vulcanizate (TPV) elastomer, a polyurethane elastomer, a block copolymer elastomer, a polyolefin blend elastomer, a thermoplastic co-polyester elastomer, a thermoplastic polyamide elastomer, or a combination thereof (e.g., a blend of at least two of the listed soft polymeric materials). The soft polymer layers can be the same material or a different material. In certain embodiments, the first soft polymer layer and the second soft polymer layer are the same polymeric material.

The soft polymer layers of the appliances can have a variety of physical properties. For example, physical properties such as hardness, ultimate tensile strength, elongation 20 at break, tensile modulus, compression set, flexural modulus, and light transmission can each be specifically tailored for a particular application. In some embodiments, the soft polymer layers of the appliances can independently have a physical property of at least one of a hardness of about 60 A to about 85 D, an ultimate tensile strength of greater than about 5000 psi, an elongation at break of greater than about 200%, a compression set at about 70° C. of greater than 40% after 24 hours, a flexural modulus of greater than about 35,000 psi, and a light transmission between 400 nm and 800 nm of greater than about 75%.

As described herein, the layers of the appliances can include a hard polymer layer disposed between two soft polymer layers. In one embodiment, the multilayer appliances can include a hard polymer layer of one type of material (e.g., a co-polyester), and two soft polymer layers of other types of material that can be the same or different (e.g., two soft polymer layers of thermoplastic polyurethane elastomer). In some embodiments, the multilayer appliances can also include a hard polymer layer of at least two layers of polymer material. For example, the hard polymer layer can include several polymer layers laminated together to form the hard polymer layer. The laminated hard polymer layer can include at least two layers of any combination of the following polymer materials: a polyester, a co-polyester, a polycarbonate, a thermoplastic polyurethane, a polypropylene, a polyethylene, a polypropylene and polyethylene copolymer, an acrylic, a cyclic block copolymer, a polyetheretherketone, a polyamide, a polyethylene terephthalate, a polybutylene terephthalate, a polyetherimide, a polyethersulfone, and a polytrimethylene terephthalate. Similarly, in some embodiments, the multilayer appliances can include a soft polymer layer of at least two layers of polymer material. For example, the soft polymer layers 22, 26 can include a layer of several polymer layers 22-1, 22-2, 22-N and 26-1, 26-2, 26-N, respectively, laminated together. The laminated soft polymer layers can include at least two layers of any combination of the following polymer materials: a styrenic block copolymer (SBC), a silicone rubber, an elastomeric alloy, a thermoplastic elastomer (TPE), a thermoplastic vulcanizate (TPV) elastomer, a polyurethane elastomer, a block copolymer elastomer, a polyolefin blend elastomer, a thermoplastic co-polyester elastomer, and a thermoplastic polyamide elastomer.

The tooth positioning appliances can be fabricated using a variety of methods. For example, methods for making the appliances can include thermoforming a multilayer sheet into an aligner by heating the sheet and then molding the

Document 1-2

sheet to a particular configuration. Exemplary methods for fabricating the appliances, including those utilized in the Invisalign® System, are described in numerous patents and patent applications assigned to Align Technology, Inc. including, for example, in U.S. application Ser. No. 13/186, 5 374 as well as on the company's website, which is accessible on the World Wide Web (see, e.g., the url invisalign.com").

FIG. 3 depicts an example embodiment of a process 30 for forming a multilayer tooth positioning appliance, in accordance with an embodiment of the present invention. As shown, a multilayer sheet 32 can be formed into a tooth positioning appliance 36. The multilayer sheet 32, as depicted, can include three layers: a hard polymer layer disposed between two soft polymer layers. In this example process, the tooth positioning appliance 36 can be produced 15 with the use of a physical tooth model, or mold, 34. The tooth positioning appliance 36 can be produced by heating the thermoformable multilayer sheet 32 and then vacuum or pressure forming the sheet over the teeth in the physical tooth model 34. The tooth positioning appliance 36 is a 20 direct representation of the physical tooth model. Excess material from the sheet can be trimmed to form a final tooth positioning appliance that can be used for orthodontic treatment of a patient.

One or a series of physical tooth models, such as the 25 model described above, may be used in the generation of elastic repositioning appliances for orthodontic treatment. Similar to the process above, each of the appliances can be generated by thermoforming a multilayer polymeric material over a mold of a desired tooth arrangement to form a 30 dental appliance. The tooth positioning appliance of the desired tooth arrangement generally conforms to a patient's teeth but is slightly out of alignment with the initial tooth configuration. Placement of the elastic positioner over the teeth applies controlled forces in specific locations to gradu- 35 ally move the teeth into the desired configuration. Repetition of this process with successive appliances comprising new configurations eventually moves the teeth through a series of intermediate configurations to a final desired configuration.

The present invention includes a variety of methods for 40 fabricating dental appliances. FIG. 4 shows a simple schematic for a method 40 of fabricating a removable orthodontic tooth positioning appliance having teeth receiving cavities shaped to directly receive at least some of the patient's teeth and apply a resilient positioning force to the patient's 45 teeth, in accordance with an embodiment of the present invention. The method can include providing a multilayer sheet having a hard polymer layer disposed between two soft polymer layers (Step 42). The method can further include providing a positive physical model of a patient's teeth (Step 50 44). The tooth positioning appliance can be fabricated by thermoforming the multilayer sheet over the positive physical model (Step 46), in which the tooth positioning appliance is a negative of the positive model. As described above, the methods of fabrication can further include trimming or 55 cutting portions of the sheet to render a final, usable appliance for orthodontic treatment.

Multilayer sheets of the present invention were analyzed and determined to provide a variety of improved properties for aligners used in orthodontic treatment. As further 60 described herein, the multilayer sheets formed into aligners can, for example, provide increased durability of the aligners so that they can better withstand wear due to teeth grinding and other mechanical stresses put on the aligner during treatment. In addition, the aligners have improved elastic 65 properties that allow for less degradation in the shape of the teeth receiving cavities during a stage of treatment. For

8

example, during a multistage orthodontic treatment, the capability of an aligner to force tooth movement can degrade and may cause the treatment to include more aligners to reach a final ideal arrangement and/or result in a mid-course correction that could be prevented by using aligners with improved physical properties, such as those provided herein.

FIGS. 5-8 provide example test results that compare various physical properties of the multilayer sheet appliances of the present invention with other already existing aligner materials (Material 1). Samples of varied thicknesses were tested. For example, multilayer sheets were tested having a hard polymer layer with thicknesses ranging from about 580 □m to about 715 □m thick. In some examples, the hard layer was a co-polyester hard polymer layer. The soft layers tested ranged between about 50 □m to about 100 ☐m. In some examples, the hard polymer layer was disposed between thermoplastic polyurethane elastomer soft polymer layers. As shown in FIGS. 5 and 6, one example of the multilayer sheet material (Material 2) showed improved stress relaxation properties as compared to another already existing material (Material 1) at room temperature and 37° C. In addition, FIG. 7 shows improved long-term unloading characteristics of the multilayer sheet Material 2 versus the already existing Material 1. The multilayer sheet showed less deflection under force loads. FIG. 8 also shows improved long-term movement data for the multilayer sheet Material 2 versus Material 1.

The use of the terms "a" and "an" and "the" and similar referents in the context of describing embodiments (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms "comprising," "having," "including," and "containing" are to be construed as open-ended terms (i.e., meaning "including, but not limited to,") unless otherwise noted. The term "connected" is to be construed as partly or wholly contained within, attached to, or joined together, even if there is something intervening. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., "such as") provided herein, is intended merely to better illuminate embodiments and does not pose a limitation on the scope unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of at least one embodiment.

Variations of the embodiments described herein may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate, and the inventors intend for embodiments to be constructed otherwise than as specifically described herein. Accordingly, suitable embodiments include all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is contemplated as being incorporated into some suitable embodiment unless otherwise indicated herein or otherwise clearly contradicted by context. The scope of the invention should, therefore, be determined not with reference to the above description, but instead should be

9

Case 6:24-cv-00187-ADA-DTG

determined with reference to the pending claims along with their full scope or equivalents.

What is claimed is:

- 1. A dental appliance for positioning a patient's teeth from a first arrangement toward a second arrangement, the dental appliance comprising:
 - a plurality of tooth-receiving cavities shaped to receive and resiliently reposition the patient's teeth from the $\frac{10}{10}$ first arrangement toward the second arrangement;
 - three or more polymer layers, the three or more polymer layers comprising:
 - a hard polymer layer comprising a co-polyester and having a flexural modulus greater than about 150, $_{15}$ 000 psi; and
 - a soft polymer layer comprising a thermoplastic polyurethane elastomer and having an elongation at break of greater than about 200%, and a hardness from about 60 A to about 85 D.
- 2. The dental appliance of claim 1, wherein the soft polymer layer has an ultimate tensile strength of greater than about 5000 psi.
- 3. The dental appliance of claim 1, wherein the hard polymer layer has an ultimate tensile strength of greater than 25 150,000 psi.
- 4. The dental appliance of claim 1, wherein the hard polymer layer has a tensile modulus greater than 150,000
- 5. The dental appliance of claim 1, wherein the soft 30 polymer layer has a flexural modulus of greater than about 35,000 psi.
- 6. The dental appliance of claim 1, wherein the hard polymer layer has a tensile strength at yield between 4000 psi and 6500 psi.
- 7. The dental appliance of claim 1, wherein the hard polymer layer has an elongation at break of greater than
- 8. The dental appliance of claim 1, wherein the hard polymer layer has a hard polymer layer elastic modulus and 40 the soft polymer layer has a soft polymer layer elastic modulus less than the hard polymer layer elastic modulus.
- 9. The dental appliance of claim 1, wherein the soft polymer layer has a compression set greater than 40% after 24 hours at 70° C.
- 10. The dental appliance of claim 1, wherein the dental appliance has a thickness of between 500 um and 1200 um.
- 11. A plurality of dental appliances for positioning a patient's teeth, having a plurality of tooth-receiving cavities shaped to directly receive at least some of the patient's teeth 50 and apply a resilient positioning force to the patient's teeth, wherein the plurality of dental appliances are shaped to move teeth from one arrangement to a successive arrangement, and wherein at least at one of the plurality of dental appliances comprises:
 - three or more polymer layers, the three or more polymer layers comprising:
 - a hard polymer layer comprising a co-polyester and having a flexural modulus greater than about 150,000 psi; and
 - a soft polymer layer comprising a thermoplastic polyurethane elastomer and having an elongation at break of greater than about 200%, and a hardness from about 60 A to about 85 D.
- 12. The plurality of dental appliances of claim 11, wherein 65 the soft polymer layer has an ultimate tensile strength of greater than about 5000 psi.

10

- 13. The plurality of dental appliances of claim 11, wherein the hard polymer layer has an ultimate tensile strength of greater than 150,000 psi.
- 14. The plurality of dental appliances of claim 11, wherein the hard polymer layer has a tensile modulus greater than 150,000 psi.
- 15. The plurality of dental appliances of claim 11, wherein the soft polymer layer has a flexural modulus of greater than about 35,000 psi.
- 16. The plurality of dental appliances of claim 11, wherein the hard polymer layer has a tensile strength at yield between 4000 psi and 6500 psi.
- 17. The plurality of dental appliances of claim 11, wherein the hard polymer layer has an elongation at break of greater than about 70%.
- 18. The plurality of dental appliances of claim 11, wherein the hard polymer layer has a hard polymer layer elastic modulus and the soft polymer layer has a soft polymer layer elastic modulus less than the hard polymer layer elastic 20 modulus.
 - 19. The plurality of dental appliances of claim 11, wherein the soft polymer layer has a compression set greater than 40% after 24 hours at 70° C.
 - 20. The plurality of dental appliances of claim 11, wherein at least one of the dental appliances has a thickness of between 500 μm and 1200 μm.
 - 21. A plurality of dental appliances for positioning a patient's teeth, the plurality of dental appliances comprising: a first dental appliance comprising:
 - a first plurality of tooth-receiving cavities shaped to receive and resiliently reposition the patient's teeth from a first arrangement toward a second arrangement:
 - first three or more polymer layers, the first three or more polymer layers comprising:
 - a first hard polymer layer comprising a co-polyester and having a flexural modulus greater than about 150,000 psi; and
 - a first soft polymer layer comprising a thermoplastic polyurethane elastomer and having an elongation at break of greater than about 200%, and a hardness from about 60 A to about 85 D; and
 - a second dental appliance comprising:
 - a second plurality of tooth-receiving cavities shaped to receive and resiliently reposition the patient's teeth from the second arrangement toward a third arrangement:
 - second three or more polymer layers, the second three or more polymer layers comprising:
 - a second hard polymer layer comprising a co-polyester and having a flexural modulus greater than about 150,000 psi; and
 - a second soft polymer layer comprising a thermoplastic polyurethane elastomer and having an elongation at break of greater than about 200%, and a hardness from about 60 A to about 85 D.
 - 22. The plurality of dental appliances of claim 21, wherein the first soft polymer layer and the second soft polymer layer has an ultimate tensile strength of greater than about 5000 psi
 - 23. The plurality of dental appliances of claim 21, wherein the first hard polymer layer and the second hard polymer layer has an ultimate tensile strength of greater than 150,000 psi.
 - 24. The plurality of dental appliances of claim 21, wherein the first hard polymer layer and the second hard polymer layer has a tensile modulus greater than 150,000 psi.

12

US 11,154,384 B2

11

- **25**. The plurality of dental appliances of claim **21**, wherein the first soft polymer layer and the second soft polymer layer has a flexural modulus of greater than about 35,000 psi.
- **26**. The plurality of dental appliances of claim **21**, wherein the first hard polymer layer and the second hard polymer 5 layer has a tensile strength at yield between 4000 psi and 6500 psi.
- 27. The plurality of dental appliances of claim 21, wherein the first hard polymer layer and the second hard polymer layer has an elongation at break of greater than about 70%. 10
- 28. The plurality of dental appliances of claim 21, wherein:
 - the first hard polymer layer and the second hard polymer layer has a hard polymer layer elastic modulus; and the first soft polymer layer and the second soft polymer 15 layer has a soft polymer layer elastic modulus, wherein the soft polymer layer elastic modulus is less than the hard polymer layer elastic modulus.
- **29**. The plurality of dental appliances of claim **21**, wherein the first soft polymer layer and the second soft polymer layer 20 has a compression set greater than 40% after 24 hours at 70° C.
- 30. The plurality of dental appliances of claim 21, wherein at least one of the first dental appliance or second dental appliance dental appliance has a thickness of between 500 $\,$ 25 $\,$ μm and 1200 $\,\mu m$.

* * * * *